

The PipeHugger /HP Range by PulseGuard

— ORDERING —		Inch / "Standard"		1 Connection			2 Connections			Specification			Price one. Piece \$	Spares Kit SK/-?=Elast EP, N(Buna), Hyp, V(Fluoro)
Liquid in Bladder	Gas in Steel drive bonnet	In	3	DP @ 200F PSI	Ansi B16.5 Largest Bolt Circle Diam.	To pump x To system	Fem. & Male NPT	L in	D in	lbs				
PHr-TW-ss		8		10000	1/2" 2500	1/8"x1/8"	NF	6.7	4	14		D64y42 ?		
PHr-TW-ss		18		10000	3/4" 2500	3/8"x3/8"	NF	8.75	4.5	33		D77y53 ?		
PHr-TW-ss		40		3600	1" 1500	1/2"x3/8"	NF	8.9	5	28		D100y60?		
PHr-TW-ss		40		6500	1" 2500	1/2"x1/2"	NF	11	5.9	52		D100y60?		
PHr-TW-ss		61		2000	1/2" 600#	3/4"x1/2"	NF	9.8	6.6	48		D125y65?		
PHr-TW-ss		61		5800	1/2" 1500#	3/4"x3/4"	NF	11.2	7	68		D125y65?		
PHr-TW-ss		122		2000	3/4" 1500#	3/4"x3/4"	NF	9.4	6.6	44		D145y75?		
PHr-TW-ss		122		5000	1" 2500#	1.0"x1.0"	NF	13	7.9	112		D150y80?		
PHr-TW-ss		183		3150	1.5" 1500#	1.5"Mx1.0"	NF	11.2	8.5	99		D176y90?		
PHr-TW-ss		213		1700	2.5" 600#	1.5"NMx1.5"	NM	9.6	8.5	57		D191y95?		
PHr-TW-ss		488		2900	2" 1500#	2"NMx1.5"	NM	14.9	10.6	158		D225y110?		
PHr-TW-ss		503		1400	3.5" 600#	2"NMx2"	NM	12.4	10.7	149		D238y110?		
PHr-TW-ss		610		1900	3" 900#	2"NMx2"	NM	14	10.7	231		D238y110?		
PHr-TW-ss		610		3050	2.5" 1500#	2"NMx2"	NM	12.7	12.7	266		D254y118?		
PHr-TW-ss		854		1750	4" 900#	3"NMx2"	NM	15	12.7	216		D285y128?		
PHr-TW-ss		915		3100	3" 1500#	3"NMx2"	NM	16.7	13.9	488		D285y128?		
PHr-TW-ss		1220		1200	5" 600#	4"Wx4"W _{37.5} ⁰ 45x45		14.4	13.9	286		D328y123?		
PHr-TW-ss		1220		3050	4" 1500#	4"Wx4"W _{37.5} ⁰ 45x45		18.4	15.9	748		D328y123?		
PHr-TW-ss		1830		1600	5" 900#	5"Wx5"W _{37.5} ⁰ 45x45		22	15.9	411		D368y178?		
PHr-TW-ss		1830		3400	4" 2500#	5"Wx5"W _{37.5} ⁰ 45x45		25	17.9	1075		D368y178?		
PHr-TW-ss		2440		1450	8" 600#	6"Wx6"W _{37.5} ⁰ 45x45		24	19.9	800		D450y120?		
PHr-TW-ss		2440		3375	6" 1500#	6"Wx6"W _{37.5} ⁰ 45x45		28	21.9	1577		D450y120?		