

PULSEGUARD® Guard against Pulsation




PULSEGUARD is the registered UK trademark of PulseGuard Ltd.
PULSEGUARD is the registered US trademark of PulseGuard Inc.

PUMPS make FLOW, BUT SYSTEMS make PRESSURE, PULSATION is a system pressure response, and a SYSTEM RESPONSIBILITY, not a pump manufacturer liability.


PulseGuard Pulsation Dampers of the following types shown on PG 143,144, 145, and 146, the PipeHugger, PipeGuard, and PumpGuard ranges, have removable ends. generally in accordance ASME VIII Div1 UG34 (m). The end plug lock ring retention is dimensioned to provide a safety release. It is necessary to withdraw these end plugs keeping the centerline axis of the plug true with the axis of the cylinder from which they are being withdrawn. If this care is omitted the cylinder bore may be scratched, preventing sealing with the replacement "O" ring. Never re-use an O ring.

"XTRACTOR" RIGS FOR A STRAIGHT WITHDRAWAL, OF END PLUGS.

SEQUENCE




"CENTER PULL"




Call factory for dims, to make your own, or to order. € or \$s

- XTRACTOR XT1950 upto units 450mm ID
- XTRACTOR XT733 upto units 285mm ID
- XTRACTOR XT122 upto units 150mm ID



A "Half-Ring" set is half the thickness of the units tamper-proof lock-ring. The Half-Ring fills the lock-ring groove, and provides a smooth surface with chamfered corners to ease the slide-out of seals and membrane edges.



Dampers that do. Flow goes through. BUT Pressure Pulsation does not.



PULSEGUARD®
Guard against Pulsation

UK Colour & BW FreeFax 0800-174-088 , Internat. --44(0)161-443-1486
Color fax is 10 times faster than email attach, and there are no viruses.
UK FreePhone 08080-567-7423 , Internat. --44(0)161-442-6222
USA: BW & Color Fax, --01(1)910-270-0320 FreeFax 1-888-825-5357
Toll Free 1-888-DAMPERS (326-7377), The Americas --01(1)910-270-2737

